

Navy Tech

- Explosion Proof Flood Light suitable for Hazardous Areas Zone 1 & Zone 2
- Heavy Duty stainless steel bracket SS316L
- 4mm thick tempered glass
- + 95% light transmission
- L70 (hrs) rated > 60.000 hours
- Heat Dissipation design
- High Performance LED chips
- Extreme Durability IP67, Anti-Corrosion WF2, Water-Proof, Dust-Proof
- Heat Protection with separated cavities for the driver & the LED chips



	Navy Teck -40	Navy Teck -100	Navy Teck -200
Wattage	30 W 40 W, 50 W	60 W, 80 W, 100 W	120 W, 150 W, 185 W
Input voltage	100-277V, 50/60Hz	100-277V, 50/60Hz	100-277V, 50/60Hz
Color/CCT	3000 K - 6500 K	3000 K - 6500 K	3000 K - 6500 K
CRI	>Ra85	>Ra85	>Ra85
Lumen	3.600 - 6.000	7.200 - 12.000	14.400 - 22.200
Beam angle	30°/60°/90°/120°	30°/60°/90°/120°	30°/60°/90°/120°
Lifetime	>60.000 hours	>60.000 hours	>60.000 hours
Operating temperature	-30°C to +50°C	-30°C to +55°C	-30°C to +50°C
Warranty	3 years	3 years	3 years

